

BONDERITE L-GP YA ACHESON

Known as Gredag YA
August 2015

PRODUCT DESCRIPTION

BONDERITE L-GP YA ACHESON provides the following product characteristics:

Technology	Lubricant
Product Type	Graphited grease
Application	Forging and extrusion lubricant

BONDERITE L-GP YA ACHESON is a graphited lanolin based grease within NLGI 4 specification. BONDERITE L-GP YA ACHESON is used as a swab applied die lubricant in hot forming operations, most notably in hot stamping of brass. BONDERITE L-GP YA ACHESON is often used where lubricant spray application is not economic, as in small quantity production, or where high tool temperatures are required. This leads to use in hot and warm extrusion of steel, aluminium and copper alloys.

Special features

- The high covering power allows sparing use.
- The consistency makes application of thin coatings possible.
- High purity graphite extends tool life.
- Superior film adhesion allows much metal flow.
- The use in thin films allows high precision.
- The soft texture makes swabbing easy.
- Soft greases allow more complete utilisation of the contents of a container, less lubricant is thrown away.
- Good spreading makes application of excessively thick films difficult.

Application Areas:

- Hot forming operations, most notably in hot stamping of brass.
- Hot and warm extrusion of steel, aluminium and copper alloys.

TECHNICAL DATA

(as supplied)

Lubricant	high purity micro-graphite
Carrier	lanolin base
NLGI No.	4
Penetration	160 to 210
Flash Point, °C	220

DIRECTION OF USE

Preliminary Statement:

Prior to use it is necessary to read the **Material Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed. Please also refer to the local safety instructions and contact Henkel for analytical support.

Application:

BONDERITE L-GP YA ACHESON is ready-for-use. Its NLGI No. 4 consistency promotes an easy and sparing use.

BONDERITE L-GP YA ACHESON is applied to the tooling by swab or brush from once per cycle for difficult parts on hot running tools to a few times per hour for simple light parts.

Storage:

Recommended Storage Temperature, °C	5 to 40
Shelf life, months (in unopened original packaging)	24

Classification:

Please refer to the corresponding **Material Safety Data Sheets** for details on:

- Hazards identification**
- Transport information**
- Regulatory information**

ADDITIONAL INFORMATION**Disclaimer****Note:**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage: [Except as otherwise noted] All trademarks in this document are trademarks and/or registered trademarks of Henkel and its affiliates in the U.S. and elsewhere.

Reference 0.0