

BONDERITE L-GP 580 ACHESON

Known as Dag 580
July 2019

PRODUCT DESCRIPTION

BONDERITE L-GP 580 ACHESON provides the following product characteristics:

Technology	Lubricant
Product Type	Graphite dispersion in solvent
Application	Multi purpose

BONDERITE L-GP 580 ACHESON is a colloidal dispersion of specially processed micro-graphite in ethyl alcohol. It is used for the formation of dry lubricating films and electrically conducting coatings. It is also employed as an anti-seize material on screw threads.

Application:

Dry Film Lubrication

The product is particularly suitable for operation under high loads at normal temperatures, e.g. machines for cigarette manufacture and food handling where no traces of any unpleasant odour can be tolerated; office machines, vending machines, parking meters.

Electrically Conducting Coatings

Applications include plastic cable treatment; prevention of corona discharge in electrical equipment; electrostatic screening particularly of plastic surfaces; as an electrode in radiation meters and counters; in industrial and radio valves on grids and anodes.

Screw Thread Treatment

Normally the product is applied by means of a soft brush after dilution to a suitable consistency. The advantage of the product is the rapid evaporation of the volatile carrier liquid. It is essential that the surfaces to be coated should first be cleaned and degreased.

Other Applications

Impregnation of porous materials and incorporation into resins and plastics.

TECHNICAL DATA

Solids content, %	~23		
Density, kg/m ³	900		
Flash Point, °C	14		
Diluent	butanol, acetate, alcohol	toluene, industrial	butyl- ethyl

DIRECTION OF USE

Preliminary Statement:

Prior to use it is necessary to read the **Material Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed. Please also refer to the local safety instructions and contact Henkel for analytical support.

Pretreatment:

Surfaces to be coated should first be cleaned and degreased. On highly polished surfaces a roughening pretreatment like sand blasting or etching will improve adhesion.

Dilution:

BONDERITE L-GP 580 ACHESON must be diluted by slowly adding the diluent to the concentrate, under continuous stirring. The concentrate should be stirred well before it is taken out of its original container.

Application:

After dilution BONDERITE L-GP 580 ACHESON can be applied by spray, brush or dip methods.

The following dilution ratios per volume of product are recommended:

Brush: 1 to 3 volumes of diluent
Spray: up to 8 volumes of diluent
Dip: 1 to 4 volumes of diluent

The diluted product should be stirred before use to maintain a homogeneous suspension.

The films are ready for service after air drying for 1 hour.

Curing:

Depending on the nature of the substrate the films may be cured for 10 min. to 1 hour, at a maximum temperature of 150 °C.

Classification:

Please refer to the corresponding **Material Safety Data Sheets** for details on:

Hazards identification
Transport information
Regulatory information

Storage:

Recommended Storage Temperature, °C 8 to 28
Shelf-life, months 48
(in unopened original packaging)



ADDITIONAL INFORMATION

Disclaimer

Note:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 1.1