

## BONDERITE® L-CA CP 799 ACHESON

February 2026

### PRODUCT DESCRIPTION

BONDERITE® L-CA CP 799 ACHESON provides the following product characteristics:

<b>Technology</b>	Lubricant
<b>Product type</b>	Release agent
<b>Application</b>	High pressure die casting

BONDERITE® L-CA CP 799 ACHESON is a high solid emulsion of specially selected release agents, for use in aluminium, zinc and magnesium pressure die-casting. BONDERITE® L-CA CP 799 ACHESON has good release properties and when used correctly allows unhindered use of subsequent painting, plating and bonding operations.

### Special features

- Silicone free
- Premium corrosion protection

Experience to date confirms that castings can be painted, plated and bonded without problem provided that oil and grease contamination of the surface has been removed.

### Application

- Release agent for pressure die casting of aluminium and magnesium alloys.
- BONDERITE® L-CA CP 799 ACHESON is perfectly suited for medium sized electrical components like light housings, UMTS sent boxes, computer and structural parts, which have to be painted or glued afterwards.
- It can be applied manually or automated, by means of reciprocators or robot based spray systems.

### TECHNICAL DATA

#### (as supplied)

Appearance	Low viscous, white fluid
Pigment	None
Carrier	Water
Diluent	Water
Solids content, %	~20

### DIRECTIONS FOR USE

#### Preliminary statement

Prior to use it is necessary to read the **Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed. Please also refer to the local safety instructions and contact Henkel for analytical support.

### Dilution

BONDERITE® L-CA CP 799 ACHESON emulsions are supplied as a concentrate to be diluted before use, allowing flexibility and economy of use. It is diluted with water, with the ratio determined by the conditions of use and the degree of die cooling required. The diluted product does not require agitation to ensure its homogeneity.

### Dilution ratio

Product can be used for pure spraying or diluted to 1 part of BONDERITE® L-CA CP 799 ACHESON to 50- 200 parts of water.

### Classification

Please refer to the corresponding **Safety Data Sheet** for details on:

- Hazards identification**
- Transport information**
- Regulatory information**

### Storage

Store BONDERITE® L-CA CP 799 ACHESON in a cool place, but do not allow it to freeze. Product should not be used once frozen.

Storage in direct sunlight may overheat BONDERITE® L-CA CP 799 ACHESON and impair performance.

Always tightly reseal the container to avoid contamination.

### Shelf life

24 months from date of qualification under original seal

**Disclaimer**

The information provided in this Technical data sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. Any liability in respect of the information in the Technical data sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

**In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:**

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

**In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

**In case products are delivered by Henkel Corporation, or Henkel Canada Corporation, the following disclaimer is applicable:**

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

**Trademark usage**

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 2