



Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 19

BONDERITE L-GP 325EF ACHESON known as EMRALON 325 EF

SDS No. : 364283
V003.0

Revision: 08.01.2018

printing date: 13.12.2018

Replaces version from: 20.03.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

BONDERITE L-GP 325EF ACHESON known as EMRALON 325 EF

Contains:

Ethyl acetate
n-Butyl acetate
Butan-1-ol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:
Dry film lubricant

1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA
Henkelstr. 67
40589 Düsseldorf

Germany

Phone: +49 (211) 797 0
Fax-no.: +49 (211) 798 4008

ua-productsafety.de@henkel.com

1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Flammable liquids	Category 2
H225 Highly flammable liquid and vapor.	
Serious eye damage	Category 1
H318 Causes serious eye damage.	
Specific target organ toxicity - single exposure	Category 3
H336 May cause drowsiness or dizziness.	
Target organ: Central Nervous System	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Signal word: Danger

Hazard statement:
H225 Highly flammable liquid and vapor.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.

Supplemental information EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statement:
Prevention P210 Keep away from sparks/open flames. - No smoking.
P261 Avoid breathing mist/vapours.
P280 Wear eye protection.

Precautionary statement:
Response P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER or doctor.
P370+P378 In case of fire: Use CO₂, dry chemical, or foam for extinction.

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Base substances of preparation:
Solvent mixture

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Ethyl acetate 141-78-6	205-500-4 01-2119475103-46	40- 60 %	Flam. Liq. 2 H225 STOT SE 3 H336 Eye Irrit. 2 H319
n-Butyl acetate 123-86-4	204-658-1 01-2119485493-29	10- < 20 %	Flam. Liq. 3 H226 STOT SE 3 H336
Cellulose nitrate 9004-70-0		5- < 10 %	Expl. 1.1 H201
Butan-1-ol 71-36-3	200-751-6 01-2119484630-38	5- < 10 %	Flam. Liq. 3 H226 Acute Tox. 4; Oral H302 STOT SE 3 H335 Skin Irrit. 2 H315 Eye Dam. 1 H318 STOT SE 3 H336
Propan-2-ol 67-63-0	200-661-7 01-2119457558-25	5- < 10 %	Flam. Liq. 2 H225 Eye Irrit. 2 H319 STOT SE 3 H336

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing.
In case of adverse health effects seek medical advice.

Eye contact:

Immediately flush eyes with soft jet of water or eye rinse solution for at least 5 minutes. If pains remain (intensive smarting, sensitivity to light, visual disturbance) continue flushing and contact/seek doctor or hospital.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

After eye contact: Corrosive, may cause permanent damage to eyes (impairment of vision).

Vapors may cause drowsiness and dizziness.

Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide, foam, powder
Fine water spray

Extinguishing media which must not be used for safety reasons:

Water jet (solvent-containing product).

5.2. Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in fires.

5.3. Advice for firefighters

Wear protective equipment.
Wear self-contained breathing apparatus.

Additional information:

Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid skin and eye contact.
Danger of slipping on spilled product.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Take up with liquid-absorbing material (sand).
Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact.
Ensure that workrooms are adequately ventilated.
See advice in section 8
Ground/bond container and receiving equipment.
Use explosion proof electric equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid open flames and sources of ignition.

Hygiene measures:

Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.
The workplace should be equipped with an emergency shower and eye-rinsing facility.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.
Temperatures between + 5 °C and + 30 °C

7.3. Specific end use(s)

Dry film lubricant

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Germany

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Ethyl acetate 141-78-6 [ETHYL ACETATE]	200	734	Time Weighted Average (TWA):	Indicative	ECLTV
Ethyl acetate 141-78-6 [ETHYL ACETATE]	400	1.468	Short Term Exposure Limit (STEL):	Indicative	ECLTV
Ethyl acetate 141-78-6			Short Term Exposure Classification:	Category I: substances for which the localized effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages.	TRGS 900
Ethyl acetate 141-78-6	200	730	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
n-Butyl acetate 123-86-4	62	300	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
n-Butyl acetate 123-86-4			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Butan-1-ol 71-36-3			Short Term Exposure Classification:	Category I: substances for which the localized effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages.	TRGS 900
Butan-1-ol 71-36-3	100	310	Exposure limit(s):	1 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Propan-2-ol 67-63-0	200	500	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Propan-2-ol 67-63-0			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Ethyl acetate 141-78-6	aqua (freshwater)		0,26 mg/l				
Ethyl acetate 141-78-6	aqua (marine water)		0,026 mg/l				
Ethyl acetate 141-78-6	aqua (intermittent releases)		1,65 mg/l				
Ethyl acetate 141-78-6	sewage treatment plant (STP)		650 mg/l				
Ethyl acetate 141-78-6	sediment (freshwater)				1,25 mg/kg		
Ethyl acetate 141-78-6	sediment (marine water)				0,125 mg/kg		
Ethyl acetate 141-78-6	oral				200 mg/kg		
Ethyl acetate 141-78-6	soil				0,24 mg/kg		
n-Butyl acetate 123-86-4	aqua (freshwater)		0,18 mg/l				
n-Butyl acetate 123-86-4	aqua (marine water)		0,018 mg/l				
n-Butyl acetate 123-86-4	aqua (intermittent releases)		0,36 mg/l				
n-Butyl acetate 123-86-4	sewage treatment plant (STP)		35,6 mg/l				
n-Butyl acetate 123-86-4	sediment (freshwater)				0,981 mg/kg		
n-Butyl acetate 123-86-4	sediment (marine water)				0,0981 mg/kg		
n-Butyl acetate 123-86-4	soil				0,0903 mg/kg		
n-Butyl acetate 123-86-4	Air						
n-Butyl acetate 123-86-4	Predator						
Butan-1-ol 71-36-3	aqua (freshwater)		0,082 mg/l				
Butan-1-ol 71-36-3	aqua (marine water)		0,0082 mg/l				
Butan-1-ol 71-36-3	aqua (intermittent releases)		2,25 mg/l				
Butan-1-ol 71-36-3	sewage treatment plant (STP)		2476 mg/l				
Butan-1-ol 71-36-3	sediment (freshwater)				0,178 mg/kg		
Butan-1-ol 71-36-3	sediment (marine water)				0,0178 mg/kg		
Butan-1-ol 71-36-3	soil				0,015 mg/kg		
Propan-2-ol 67-63-0	aqua (freshwater)		140,9 mg/l				
Propan-2-ol 67-63-0	aqua (marine water)		140,9 mg/l				
Propan-2-ol 67-63-0	sediment (freshwater)				552 mg/kg		
Propan-2-ol 67-63-0	sediment (marine water)				552 mg/kg		
Propan-2-ol 67-63-0	soil				28 mg/kg		
Propan-2-ol 67-63-0	aqua (intermittent releases)		140,9 mg/l				
Propan-2-ol 67-63-0	sewage treatment plant		2251 mg/l				

	(STP)						
Propan-2-ol 67-63-0	oral				160 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Ethyl acetate 141-78-6	Workers	inhalation	Acute/short term exposure - systemic effects		1468 mg/m ³	
Ethyl acetate 141-78-6	Workers	inhalation	Acute/short term exposure - local effects		1468 mg/m ³	
Ethyl acetate 141-78-6	Workers	dermal	Long term exposure - systemic effects		63 mg/kg	
Ethyl acetate 141-78-6	Workers	inhalation	Long term exposure - systemic effects		734 mg/m ³	
Ethyl acetate 141-78-6	Workers	inhalation	Long term exposure - local effects		734 mg/m ³	
Ethyl acetate 141-78-6	General population	Inhalation	Acute/short term exposure - systemic effects		734 mg/m ³	
Ethyl acetate 141-78-6	General population	inhalation	Acute/short term exposure - local effects		734 mg/m ³	
Ethyl acetate 141-78-6	General population	dermal	Long term exposure - systemic effects		37 mg/kg	
Ethyl acetate 141-78-6	General population	inhalation	Long term exposure - systemic effects		367 mg/m ³	
Ethyl acetate 141-78-6	General population	oral	Long term exposure - systemic effects		4,5 mg/kg	
Ethyl acetate 141-78-6	General population	inhalation	Long term exposure - local effects		367 mg/m ³	
n-Butyl acetate 123-86-4	Workers	inhalation	Long term exposure - systemic effects		300 mg/m ³	
n-Butyl acetate 123-86-4	Workers	inhalation	Acute/short term exposure - systemic effects		600 mg/m ³	
n-Butyl acetate 123-86-4	Workers	inhalation	Long term exposure - local effects		300 mg/m ³	
n-Butyl acetate 123-86-4	Workers	inhalation	Acute/short term exposure - local effects		600 mg/m ³	
n-Butyl acetate 123-86-4	Workers	dermal	Long term exposure - systemic effects		11 mg/kg	
n-Butyl acetate 123-86-4	Workers	dermal	Acute/short term exposure - systemic effects		11 mg/kg	
n-Butyl acetate 123-86-4	General population	inhalation	Long term exposure - systemic effects		35,7 mg/m ³	
n-Butyl acetate 123-86-4	General population	inhalation	Acute/short term exposure - systemic effects		300 mg/m ³	
n-Butyl acetate 123-86-4	General population	inhalation	Acute/short term exposure - local effects		300 mg/m ³	
n-Butyl acetate 123-86-4	General population	dermal	Long term exposure - systemic effects		6 mg/kg	
n-Butyl acetate 123-86-4	General population	dermal	Acute/short term exposure - systemic effects		6 mg/kg	
n-Butyl acetate 123-86-4	General population	oral	Long term exposure - systemic effects		2 mg/kg	
n-Butyl acetate 123-86-4	General population	oral	Acute/short term exposure -		2 mg/kg	

			systemic effects			
n-Butyl acetate 123-86-4	General population	inhalation	Long term exposure - local effects		35,7 mg/m ³	
Butan-1-ol 71-36-3	Workers	Inhalation	Long term exposure - local effects		310 mg/m ³	
Butan-1-ol 71-36-3	General population	oral	Long term exposure - systemic effects		3,125 mg/kg	
Butan-1-ol 71-36-3	General population	Inhalation	Long term exposure - local effects		55 mg/m ³	
Propan-2-ol 67-63-0	Workers	dermal	Long term exposure - systemic effects		888 mg/kg	
Propan-2-ol 67-63-0	Workers	inhalation	Long term exposure - systemic effects		500 mg/m ³	
Propan-2-ol 67-63-0	General population	dermal	Long term exposure - systemic effects		319 mg/kg	
Propan-2-ol 67-63-0	General population	inhalation	Long term exposure - systemic effects		89 mg/m ³	
Propan-2-ol 67-63-0	General population	oral	Long term exposure - systemic effects		26 mg/kg	

Biological Exposure Indices:

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
Butan-1-ol 71-36-3	1-butanol	Creatinine in urine	Sampling time: Prior to shift.	2 mg/g	DE BAT		
Butan-1-ol 71-36-3	1-butanol	Creatinine in urine	Sampling time: End of shift.	10 mg/g	DE BAT		
Butan-1-ol 71-36-3	1-Butanol (with hydrolysis)	Creatinine in urine	Sampling time: Prior to shift.	2 mg/g	DE BGW		
Butan-1-ol 71-36-3	1-Butanol (with hydrolysis)	Creatinine in urine	Sampling time: End of shift.	10 mg/g	DE BGW		
Propan-2-ol 67-63-0	acetone	Blood	Sampling time: End of shift.	25 mg/l	DE BGW		
Propan-2-ol 67-63-0	acetone	Urine	Sampling time: End of shift.	25 mg/l	DE BGW		

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/suction at the workplace.

Respiratory protection:

In case of aerosol formation, we recommend wearing of appropriate respiratory protection equipment with ABEK P2 filter (EN 14387).

This recommendation should be matched to local conditions.

Hand protection:

Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): Isobutylene-isoprene rubber (IIR; >= 0.7 mm thickness) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): Isobutylene-isoprene rubber (IIR; >= 0.7 mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:
Protective eye equipment should conform to EN166.
Goggles which can be tightly sealed.

Skin protection:
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.
Suitable protective clothing

Advices to personal protection equipment:
The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.
Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	liquid liquid Milky white
Odor	Solvent
Odour threshold	No data available / Not applicable
pH	Not applicable
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	77 °C (170.6 °F)
Flash point	-7 °C (19.4 °F); no method
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	
lower	1,2 % (V)
upper	11,5 % (V)
Vapour pressure (50 °C (122 °F))	220 mbar
Vapour pressure (55 °C (131 °F))	280 mbar
Relative vapour density:	No data available / Not applicable
Density (20 °C (68 °F))	0,98 g/cm ³
Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative) (Solvent: Water)	Insoluble
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity (Brookfield; Instrument: RVT; 20 °C (68 °F); speed of rotation: 20 min ⁻¹)	260 - 400 mPa.s
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Reaction with strong oxidants.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

No decomposition if used according to specifications.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

None if used for intended purpose.

In case of fire toxic gases can be released.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Ethyl acetate 141-78-6	LD50	6.100 mg/kg	rat	not specified
n-Butyl acetate 123-86-4	LD50	10.760 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
Cellulose nitrate 9004-70-0	LD50	> 5.000 mg/kg	rat	not specified
Butan-1-ol 71-36-3	LD50	790 mg/kg	rat	not specified
Propan-2-ol 67-63-0	LD50	5.840 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Ethyl acetate 141-78-6	LD50	> 20.000 mg/kg	rabbit	Draize Test
n-Butyl acetate 123-86-4	LD50	> 14.112 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Butan-1-ol 71-36-3	LD50	3.430 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Propan-2-ol 67-63-0	LD50	12.870 mg/kg	rabbit	not specified

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Ethyl acetate 141-78-6	LC50	200 mg/l		1 h	rat	not specified
n-Butyl acetate 123-86-4	LC50	> 23,4 mg/l	mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
Propan-2-ol 67-63-0	LC50	72,6 mg/l		4 h	rat	not specified

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Ethyl acetate 141-78-6	slightly irritating	24 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
n-Butyl acetate 123-86-4	not irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Butan-1-ol 71-36-3	irritating	2 h	rabbit	not specified
Propan-2-ol 67-63-0	slightly irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Ethyl acetate 141-78-6	slightly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
n-Butyl acetate 123-86-4	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Butan-1-ol 71-36-3	Category 1 (irreversible effects on the eye)		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Propan-2-ol 67-63-0	moderately irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Ethyl acetate 141-78-6	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
n-Butyl acetate 123-86-4	not sensitising	Guinea pig maximisation test	guinea pig	not specified
Butan-1-ol 71-36-3	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	not specified
Butan-1-ol 71-36-3	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Propan-2-ol 67-63-0	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Ethyl acetate 141-78-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Ethyl acetate 141-78-6	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
n-Butyl acetate 123-86-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
n-Butyl acetate 123-86-4	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Butan-1-ol 71-36-3	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		Ames Test
Butan-1-ol 71-36-3	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Propan-2-ol 67-63-0	negative with metabolic activation	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Ethyl acetate 141-78-6	negative	oral: gavage		hamster, Chinese	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
n-Butyl acetate 123-86-4	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Butan-1-ol 71-36-3	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Propan-2-ol 67-63-0	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Propan-2-ol 67-63-0		inhalation: vapour	104 w 6 h/d, 5 d/w	rat	male/female	OECD Guideline 451 (Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Ethyl acetate 141-78-6	NOAEL P 1.500 mg/kg	other	inhalation: vapour	rat	other guideline:
Butan-1-ol 71-36-3	NOAEL P 2000 ppm NOAEL F1 2000 ppm	Two generation study	inhalation: vapour	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)
Propan-2-ol 67-63-0	NOAEL P 853 mg/kg	One generation study	oral: drinking water	rat	OECD Guideline 415 (One-Generation Reproduction Toxicity Study)
Propan-2-ol 67-63-0	NOAEL P 500 mg/kg NOAEL F1 1.000 mg/kg	Two generation study	oral: gavage	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Ethyl acetate 141-78-6	NOAEL 900 mg/kg	oral: gavage	90 d daily	rat	EPA OTS 795.2600 (Subchronic Oral Toxicity Test)
Ethyl acetate 141-78-6	NOAEL 1,28 mg/l	inhalation	94 d continuous	rat	EPA OTS 798.2450 (90- Day Inhalation Toxicity)
n-Butyl acetate 123-86-4	NOAEL 125 mg/kg	oral: gavage	6 (interim sacrifice) or 13 w daily	rat	EPA OTS 798.2650 (90- Day Oral Toxicity in Rodents)
Butan-1-ol 71-36-3	NOAEL 125 mg/kg	oral: gavage	13 w daily	rat	not specified
Propan-2-ol 67-63-0		inhalation: vapour	at least 104 w 6 h/d, 5 d/w	rat	not specified

Aspiration hazard:

No data available.

SECTION 12: Ecological information**General ecological information:**

Do not empty into drains / surface water / ground water.

12.1. Toxicity**Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Ethyl acetate 141-78-6	LC50	270 mg/l	48 h	Leuciscus idus melanotus	DIN 38412-15
n-Butyl acetate 123-86-4	LC50	18 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Cellulose nitrate 9004-70-0	LC50	> 1.000 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Butan-1-ol 71-36-3	LC50	1.376 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Propan-2-ol 67-63-0	LC50	> 9.640 - 10.000 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Ethyl acetate 141-78-6	EC50	164 mg/l	48 h	Daphnia cucullata	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
n-Butyl acetate 123-86-4	EC50	44 mg/l	48 h	Daphnia sp.	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Cellulose nitrate 9004-70-0	EC50	> 1.000 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Butan-1-ol 71-36-3	EC50	1.328 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Ethyl acetate 141-78-6	NOEC	2,4 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
n-Butyl acetate 123-86-4	NOEC	23,2 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Butan-1-ol 71-36-3	NOEC	4,1 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Propan-2-ol 67-63-0	NOEC	30 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Ethyl acetate 141-78-6	EC50	> 2.000 mg/l	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethyl acetate 141-78-6	NOEC	2.000 mg/l	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
n-Butyl acetate 123-86-4	EC50	674,7 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
n-Butyl acetate 123-86-4	EC10	295,5 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Cellulose nitrate 9004-70-0	ErC50	> 90.000 mg/l	72 h	Scenedesmus sp.	OECD Guideline 201 (Alga, Growth Inhibition Test)
Butan-1-ol 71-36-3	EC50	225 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Butan-1-ol 71-36-3	NOEC	129 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propan-2-ol 67-63-0	EC50	> 1.000 mg/l	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propan-2-ol 67-63-0	NOEC	1.000 mg/l	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Ethyl acetate 141-78-6	EC10	2.900 mg/l	18 h		not specified
n-Butyl acetate 123-86-4	IC50	356 mg/l	40 h	Ciliate (Tetrahymena pyriformis)	other guideline:
Cellulose nitrate 9004-70-0	EC0	1.000 mg/l	30 min		not specified
Butan-1-ol 71-36-3	EC10	2.476 mg/l	17 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)
Propan-2-ol 67-63-0	EC50	> 1.000 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Ethyl acetate 141-78-6	readily biodegradable	aerobic	100 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
n-Butyl acetate 123-86-4	readily biodegradable	aerobic	83 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Cellulose nitrate 9004-70-0	readily biodegradable	no data	> 60 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Butan-1-ol 71-36-3	readily biodegradable	aerobic	70 - 81 %	30 d	EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test)
Propan-2-ol 67-63-0	readily biodegradable	aerobic	70 - 84 %	30 d	EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test)

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
Ethyl acetate 141-78-6	0,6		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
n-Butyl acetate 123-86-4	2,3	25 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Butan-1-ol 71-36-3	1	25 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Propan-2-ol 67-63-0	0,05		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
Ethyl acetate 141-78-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
n-Butyl acetate 123-86-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Cellulose nitrate 9004-70-0	Not fulfilling PBT (persistent/bioaccumulative/toxic) criteria
Butan-1-ol 71-36-3	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Propan-2-ol 67-63-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

The product contains organic solvents which are insoluble in water. According to the requirements of the ATV regulations for the discharge of wastewater from commercial and industrial plant, organic solvents which are immiscible with water can only be discharged to an extent which corresponds to their solubility in water. The local discharge regulations take precedence.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

080111

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information**14.1. UN number**

ADR	1263
RID	1263
ADN	1263
IMDG	1263
IATA	1263

14.2. UN proper shipping name

ADR	PAINT
RID	PAINT
ADN	PAINT
IMDG	PAINT
IATA	Paint

14.3. Transport hazard class(es)

ADR	3
RID	3
ADN	3
IMDG	3
IATA	3

14.4. Packing group

ADR	II
RID	II
ADN	II
IMDG	II
IATA	II

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.6. Special precautions for user

ADR	Special provision 640D Tunnelcode: (D/E)
RID	Special provision 640D
ADN	Special provision 640D
IMDG	not applicable
IATA	not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**VOC content 80,7 %
(2010/75/EU)**15.2. Chemical safety assessment**

A chemical safety assessment has been carried out.

National regulations/information (Germany):

WGK:	WGK = 2, water endangering product. Classification according to the mixture rules in German VwVwS regulation annex 4 from 27.July 2005.
WGK:	WGK = 2, significantly water endangering mixture. Classification according to the mixture rules in German AwSV regulation annex 1, number 5.2 from 18. April 2017.
Storage class according to TRGS 510:	3

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

- H201 Explosive; mass explosion hazard.
- H225 Highly flammable liquid and vapor.
- H226 Flammable liquid and vapor.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.

Annex - Exposure Scenarios:

Exposure Scenarios for ethyl acetate can be downloaded under the following link:
http://mymsds.henkel.com/mymsds/.490394..en.ANNEX_DE.19414935.0.DE.pdf
Alternatively they can be accessed on the internet site www.mymsds.henkel.com by entering number 490394.