

BONDERITE L-FG M 1559 ACHESON

Known as DAG M-1559

April 2019

PRODUCT DESCRIPTION

BONDERITE L-FG M 1559 ACHESON provides the following product characteristics:

Technology	Lubricants
Product Type	Graphite in grease
Application	Forging die lubricant

BONDERITE L-FG M 1559 ACHESON is high temperature grease reinforced with a blend of graphite and molybdenum disulphide and is used for the lubrication of tools, dies and containers in extrusion and forging processes.

BONDERITE L-FG M 1559 ACHESON has been formulated for swab application in the extrusion of copper, steel and other metals, but also offers advantages during other processes where high pressures and temperatures at the metal/tool interface lead to breakdown of normal lubricants.

Special Features:

- Reduces die and tool wear and thus decreases down time.
- Increased extrusion ratios can be employed without lubricant failure.
- Coats tools up to 450°C.
- Permits increased output.
- Minimises pick-up and improves concentricity.
- Ideal for multi-hole practice.
- Does not run down hot surfaces and thus coatings remain in the working area.

Application Areas:

- Horizontal and vertical extrusion of copper based alloys.
- Steel forging.
- Forging and extrusion of refractory metals such as titanium.
- Hot forging of difficult-to-form components.
- Hot drawing of mild steel tube.
- Pressing of steel plates.
- Swaging of steel tubes.

TECHNICAL DATA

(as supplied):

Consistency:	soft
Specific Gravity:	1.1
Worked penetration value in 1/10 mm @ 25 °C:	250 to 290

DIRECTION OF USE

Preliminary Statement:

Prior to use it is necessary to read the **Material Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed. Please also refer to the local safety instructions and contact Henkel for analytical support.

Application:

BONDERITE L-FG M 1559 ACHESON is ready for use by swab application; it can also be applied by pumping through automatic systems.

Classification:

Please refer to the corresponding **Material Safety Data Sheets** for details on:

Hazards identification
Transport information
Regulatory information

Storage:

Recommended Storage Temperature, °C	8 to 28
Shelf life, months (in unopened original packaging)	36

ADDITIONAL INFORMATION**Disclaimer****Note:**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage: [Except as otherwise noted] All trademarks in this document are trademarks and/or registered trademarks of Henkel and its affiliates in the U.S. and elsewhere.

Reference 1.0

Henkel AG & Co. KGaA
40191 Düsseldorf, Germany
Phone: +49-211-797-0

Henkel Corporation USA
Madison Heights, MI 48071
Phone: +1-248-583-9300

Henkel (China) Co. Ltd.
201203 Shanghai, China
+86.21.2891.8000

For more information, please contact us on www.henkel.com