

# BLUESIL VACUUM GRS

<b>Description</b>	<p><b>BLUESIL VACUUM GRS</b> is a silicone paste based on polydimethyl siloxane oil and inert fillers. This paste is especially intended for use in industrial and laboratory lubrication applications. It is used to lubricate taps and valves fitted to equipment working under vacuum. It is also widely used as a high viscosity grease for valves and taps.</p>
<b>Examples of applications</b>	<ul style="list-style-type: none"> <li>• Anti-seizing: greasing of metal taps and fittings and of laboratory glassware, when a higher viscosity is required than tap grease.</li> <li>• Assembly of elastomer seals or O-rings for easy fitting and better protection in installations working under vacuum.</li> <li>• Protection of moving parts in an environment in which there is a high risk of liquid splashing. The high water repellency of silicone pastes give excellent results in terms of water wash out.</li> </ul>
<b>Key benefits</b>	<ul style="list-style-type: none"> <li>• Low vapour tension up to , enabling low residual pressure to be achieved.</li> <li>• Highly water repellent resists very well to water wash out.</li> <li>• Chemically inert: non corrosive on metals and no plasticising effect on rubbers or plastics.</li> <li>• Very little variation in viscosity as a function of temperature.</li> <li>• Resistance to extreme temperatures of between - and + in continuous use and of over when exposed for short periods.</li> <li>• Resistance to chemical agents: resists to solvents, resists oxidation and remains unaltered by mineral and vegetal oils.</li> </ul>

## Typical properties

<b>Colour</b>	Translucent to whitish
<b>Specific gravity at 25°C</b>	1.0
<b>Apparent viscosity, Pa.s</b>	7
<b>Worked penetration, 1/10th mm, approx.</b> <small>(Standards ASTM D217, NFT 6012, DIN 51804)</small>	200
<b>Unworked penetration, after 24 hours, 1/10th mm, approx.</b> <small>(Standards ASTM D217, NFT 6012, DIN 51804)</small>	190
<b>Bleeding after 24 h at 200 °C, %</b>	<0.5
<b>Evaporation after 24 h at 200 °C, %</b>	<0.5
<b>Operating temperature range, °C</b>	-40 to +200

Please note: The typical properties are not intended for use in preparing specifications. Please contact our local Sales Department for assistance in writing specifications.

<b>Instruction of use</b>	<p>It is recommended that <b>BLUESIL VACUUM GRS</b> be applied to clean dry surfaces. It may be applied using a brush, paint brush, spatula or grease gun. When applying a thin coat, it is possible to dilute the product in an aliphatic, aromatic or chlorinated solvent. Equipment may be cleaned using the same solvents.</p>
<b>Regulation</b>	Please consult your local ELKEM SILICONES sales office.
<b>Limitations</b>	Please consult your local ELKEM SILICONES sales office.
<b>Packaging</b>	<ul style="list-style-type: none"> <li>• BLUESIL VACUUM GRS is available in                             <ul style="list-style-type: none"> <li>○ Piece of 1 KG (2.21 LB)</li> <li>○ Drum of 25 KG (55.13 LB)</li> <li>○ Piece of 0.1 KG (0.22 LB)</li> </ul> </li> </ul>

# BLUESIL VACUUM GRS

---

<b>Storage and shelf life</b>	When stored in its original packaging: BLUESIL VACUUM GRS may be stored at a temperature below 40°C / 104°F for up to 36 months from its date of manufacturing. Comply with the storage instructions and expiration date marked on the packaging. Beyond this date, Elkem Silicones no longer guarantees that the product meets the sales specifications.
<b>Safety</b>	Please consult the Safety Data Sheet of: BLUESIL VACUUM GRS

---

Visit our website [www.elkem.com/silicones/](http://www.elkem.com/silicones/)

#### Warning to the users

The information contained in this document is given in good faith based on our current knowledge. It is only an indication and is in no way binding, particularly as regards infringement of or prejudice to third party rights through the use of our products. ELKEM SILICONES guarantees that its products comply with its sales specifications. This information must on no account be used as a substitute for necessary prior tests which alone can ensure that a product is suitable for given use. Determination of the suitability of product for the uses and applications contemplated by users and others shall be the sole responsibility of users. Users are responsible for ensuring compliance with local legislation and for obtaining the necessary certifications and authorisations. Users are requested to check that they are in possession of the latest version of this document and ELKEM SILICONES is at their disposal to supply any additional information.